



INDEX: ZMENY / modifications		DATE	VERSION	DATE	VERSION	DATE	VERSION	DATE	VERSION	DATE	VERSION
B	rename	12.4.16	Pam								

SOUHLAS TECHNODOKA PT approved	DATE	VERSION	TEPIJOTA PLINEN Filling temperature	≤ 15 °C	NOMINAL OBJEM Capacity fillpoint	330 ml ± 6.6 ml	POZNAKKA Remarks
SOUHVRYTYPNI VYRZAVODI FB released	DATE	VERSION	TEPIJOTA ZPRAVCOVANI Conditioning temperature	≤ 70 °C	TOTAL OBJEM Capacity brutto	350 ml ±	ZAKAZNIK Customer
VYRZAVODI	DATE	VERSION	OBSAH CO <sub>2</sub> CO <sub>2</sub> content	≤ 6 g/l	HMOTNOST Average wall thickness	205 g	PODOBNY JAKO Similar to
VYRZAVODI	DATE	VERSION	OBSAH ALKOHOLU Alcohol content	≤ 6 vol%	STREDNI TLOUSTKA STERY Average wall thickness	198 mm	NARAZUJE Replace No
NETOLEROVANE BOZKERNY DLE DIN 6129 dimensions without tolerances conform to standard DIN 6129			AXIALNI ZATIZEN Axial pressure		≤ 6 g/l	PRUKER POUJ USTIM Neck conformation dia	5B038 0330 104.2.A
			POUZITI Dispasal		MW	AW	EV
			PROCES Process		BB	PB	EPB
			BARVA Color		GR	GR	
			WITRBA PRUKER KALIBRU Mn through bore		16 mm		
			KRESLICE Scale		1:1		
			DAMA TYP Filetype		AZ		

POZNAKKA Designation	SILENUS ALE 205g KK2612 330ml LN SIL ALE 205
VYROBEK CSLO Item No	5B038 0330 104.2
Vetropack Moravia Glass a.s. CZ-69701 Knyk Tel. 00420-518 603 111 www.vetropack.com	
INDEX	B